



Revision Date: 04/21/2004

Issue date: 06/10/2004

1.	CHEMICAL	PRODUCT	AND	COMPANY	IDENTIFICATION

Item number:

 Product name:
 409 Super Bonder® Industrial Grade Gel Instant Adhesive

 Product type:
 Cyanoacrylate

Company address: Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067

Region:United StatesContact Information:Telephone: 860.571.5100Emergency telephone: 860.571.5100Internet: www.loctite.com

40904

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components Ethyl cyanoacrylate 7085-85-0

<u>%</u>	
60-100	

ACGIH TLV 0.2 ppm TWA OSHA PEL None

OTHER None

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW HMIS:				
Physical state: Color: Odor:	Liquid Clear Colorless Sharp, Irritating	HEALTH: FLAMMABILITY: PHYSICAL HAZARD: Personal Protection:	2 2 1 See Section 8	
WARNING: BONDS SKIN IN SECONDS. MAY CAUSE EYE AND RESPIRATORY IRRITATION. COMBUSTIBLE LIQUID AND VAPOR.				
Relevant routes of	exposure:	Skin, inhalation, eyes		
Potential Health Eff	ects			
Inhalation: Skin contact:		Exposure to vapors above the established exposure limit results in respiratory irritation which may lead to difficulty in breathing and tightness in the chest. Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health even if bonded to the skin.		
Eye contact: Ingestion:		Irritating to eyes. Causes excessive tearing. Eyelids may bond. Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.		
Existing conditions aggravated by exposure:		Eye, skin, and respiratory disorders.		
		See Section 11 for additional toxicological information.		

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air. If discomfort persists seek medical attention.
Skin contact:	Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.
Ingestion:	Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.
Notes to physician:	Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.
	5. FIRE-FIGHTING MEASURES
Flash point:	80°C (176°F) to 93.4°C (200°F) Tagliabue closed cup
Flash point: Autoignition temperature:	80°C (176°F) to 93.4°C (200°F) Tagliabue closed cup 485°C (905°F)
Autoignition temperature:	485°C (905°F)
Autoignition temperature: Flammable/Explosive limits-lower %:	485°C (905°F) Not determined
Autoignition temperature: Flammable/Explosive limits-lower %: Flammable/Explosive limits-upper %:	485°C (905°F) Not determined Not determined
Autoignition temperature: Flammable/Explosive limits-lower %: Flammable/Explosive limits-upper %: Extinguishing media:	485°C (905°F) Not determined Not determined Water spray (fog), foam, dry chemical or carbon dioxide.
Autoignition temperature: Flammable/Explosive limits-lower %: Flammable/Explosive limits-upper %: Extinguishing media: Special fire fighting procedures:	485°C (905°F) Not determined Not determined Water spray (fog), foam, dry chemical or carbon dioxide. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).
Autoignition temperature: Flammable/Explosive limits-lower %: Flammable/Explosive limits-upper %: Extinguishing media: Special fire fighting procedures: Unusual fire or explosion hazards:	 485°C (905°F) Not determined Not determined Water spray (fog), foam, dry chemical or carbon dioxide. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). None Trace amounts of toxic fumes may be released on incineration and the use of breathing apparatus is
Autoignition temperature: Flammable/Explosive limits-lower %: Flammable/Explosive limits-upper %: Extinguishing media: Special fire fighting procedures: Unusual fire or explosion hazards:	 485°C (905°F) Not determined Not determined Water spray (fog), foam, dry chemical or carbon dioxide. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). None Trace amounts of toxic fumes may be released on incineration and the use of breathing apparatus is recommended.

7. HANDLING AND STORAGE

	7. HANDLING AND STORAGE	
Handling:	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.	
Storage:	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.	
Incompatible products:	No special restrictions on storage with other products.	
For information	on on product shelf life contact Henkel Customer Service at (800) 243-4874.	
8. E	XPOSURE CONTROLS / PERSONAL PROTECTION	
Engineering controls:	Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.	
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).	
Skin protection:	Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.	
Eye/face protection:	Chemical splash goggles or safety glasses with side shields.	
	See Section 2 for exposure limits.	
	9. PHYSICAL AND CHEMICAL PROPERTIES	
Physical state: Color: Odor: Odor Threshold: Vapor pressure: pH: Boiling point/range: Melting point/range: Specific gravity: Vapor density: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content:	Liquid Clear Colorless Sharp, Irritating 1-2 ppm Less than 0.5 mm Hg at 25°C (77°F) Not applicable Greater than 149°C (300°F) Not determined 1.1 at 20 deg. C Approximately 3 Not available Polymerizes in presence of water Not determined Less than 20 g/L (California SCAQMD Method 316B) (estimated)	
	10. STABILITY AND REACTIVITY	
Stability:	Stable under recommended storage conditions.	
Hazardous polymerization:	Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.	
Hazardous decomposition products:	None	

Incompatability:

Conditions to avoid: Spontaneous polymerization

11. TOXICOLOGICAL INFORMATION

Water, amines, alkalis and alcohols.

Product toxicity data:

Acute oral LD50 >5000mg/kg (rat)(estimated). Acute dermal LD50 >2000mg/kg (rabbit)(estimated).

Carcinogen Status

Item number: 40904

Product name: 409 Super Bonder® Industrial Grade Gel Instant Adhesive 3 of 5

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Ethyl cyanoacrylate	No	No	No
7085-85-0			

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Ethyl cyanoacrylate	Allergen, Irritant, Respiratory
7085-85-0	

12. ECOLOGICAL INFORMATION

Ecological information:

Not known

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with Federal, State and local regulations.

EPA hazardous waste number:

Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):				
Proper shipping name:	Combustible liquids, n.o.s. (Cyanoacrylate ester)			
Hazard class or division:	Combustible liquid			
Identification number:	NA 1993			
Packing group:	None			
Exceptions:	(Not more than 450 Liters) Unrestricted			
Marine pollutant:	None			
-				
International Air Transportation (ICAO/IA	ATA):			
Proper shipping name:	Aviation regulated liquids, n.o.s (Cyanoacrylate ester)			
Hazard class or division:	9			
Identification number:	UN 3334			
Packing group:	None			
Exceptions:	(Not more than 500ml) Unrestricted			
WaterTransportation (IMO/IMDG):				
Proper shipping name:	Unrestricted			
Hazard class or division:	None			
Identification number:	None			
Packing group:	None			
Marine pollutant:	None			
·				

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 5 (a) (2) SNUR: TSCA 12 (b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None. None.	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None. Immediate Health Hazard, Delayed Health Hazard, Fire, Reactive This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). None.	
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.	
Canada Regulatory Information		
CEPA DSL/NDSL Status: WHMIS hazard class:	All components are listed on or are exempt from listing on the Domestic Substances List. B.3, D.2.B	
16. OTHER INFORMATION		

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by:

C.J. Michaels, Senior Health & Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.