



# Material Safety Data Sheet

## Section 1: Product & Company Identification

**Product Name:** Lubricure™ Concentrated Lubricity Improver

**Product Number (s):** 05712

**Manufactured By:**

CRC Industries, Inc.  
885 Louis Drive  
Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)

General Information	(215) 674-4300
Technical Assistance	(800) 521-3168
Customer Service	(800) 272-8963
24-Hr Emergency (CHEMTREC)	(800) 424-9300

## Section 2: Hazards Identification

### Emergency Overview

Appearance & Odor: Clear amber liquid, petroleum odor

### DANGER

Flammable. Harmful or Fatal if Swallowed.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

### Potential Health Effects:

**EYE:** Contact with liquid or vapor may cause mild irritation.

**SKIN:** May cause skin irritation with prolonged or repeated contact. Practically non-toxic if absorbed following a single exposure.

**INHALATION:** Excessive exposure may cause irritations to the nose, throat, lungs and respiratory tract. Central nervous system effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure and death.

**INGESTION:** Ingestion may cause gastrointestinal disturbance, including irritation, nausea, vomiting and diarrhea. The major health threat of ingestions occurs from the danger of aspiration of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia, severe lung damage and even death.

**CHRONIC EFFECTS:** Liquid may be absorbed through the skin in toxic amounts if large areas of skin are repeatedly exposed.

**TARGET ORGANS:** Central nervous system

### Medical Conditions Aggravated by Exposure:

Irritation from skin exposure may aggravate existing open wounds, skin disorders, and dermatitis.

See Section 11 for toxicology and carcinogenicity information on product ingredients.

---

**Section 3: Composition/Information on Ingredients**

COMPONENT	CAS NUMBER	% by Wt.
Petroleum distillate	68476-34-6	30 - 40
Stoddard solvent	8052-41-3	45 - 55
Tall oil fatty acid	61790-12-3	10 - 15
Isopropyl alcohol	67-63-0	3 - 6
Additive blend	Trade secret	1 - 5

---

**Section 4: First Aid Measures**

**Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

**Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

**Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

**Ingestion:** Do NOT induce vomiting. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Monitor for breathing difficulties. Mouth can be rinsed to dissipate the taste.

*Note to Physicians:* Treat symptomatically.

---

**Section 5: Fire-Fighting Measures**

Flammable Properties: As defined by OSHA, this product is a Class IC flammable liquid.

Flash Point:	80 F (TCC)	Upper Explosive Limit:	6.0
Autoignition Temperature:	500 F	Lower Explosive Limit:	1.0

**Suitable Extinguishing Media:** Use extinguishers rated for Class B fires, such as dry chemical, Halon, fire fighting foam or CO<sub>2</sub>.

**Products of Combustion:** Oxides of carbon

**Protection of Fire-Fighters:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

---

**Section 6: Accidental Release Measures**

**Personal Precautions:** Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Remove all sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

---

## Section 7: Handling and Storage

Handling Procedures: Keep away from heat, sparks and open flame. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion. Provide adequate ventilation during use. Do not breathe vapors. Wash hands after use.

Storage Procedures: Store in a cool dry area out of direct sunlight. Store in a well ventilated area. Keep out of reach of children.

Aerosol Storage Level: NA

---

## Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Petroleum Distillate	5	NE	100 (s)	NE	NE		mg/m <sup>3</sup>
Stoddard Solvent	500	NE	100	NE	NE		ppm
Tall oil fatty acid	NE	NE	NE	NE	NE		
Isopropyl alcohol	400	NE	200	400	NE		ppm
Additive blend	NE	NE	NE	NE	NE		
N.E. – Not Established      (c) – ceiling      (s) – skin      (v) – vacated							

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use NIOSH-approved self-contained positive pressure respirators in low circulation areas and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, neoprene or PVC. Also , use full protective clothing if there is prolonged or repeated contact of liquid with skin.

---

## Section 9: Physical and Chemical Properties

Physical State: liquid

Color: Clear amber

Odor: Petroleum

Specific Gravity: 0.805

Initial Boiling Point: 300 F

Freezing Point: ND

Vapor Pressure: ND

Vapor Density: &gt; 1 (air = 1)

Evaporation Rate: &lt; 1 (ether = 1)

Solubility: Negligible in water

pH: NA

Volatile Organic Compounds: wt %: 66.2 g/L: 532.9 lbs./gal: 4.44

---

**Section 10: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: temperature extremes, sources of ignition

Incompatible Materials: Strong oxidizers, strong alkalis

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, non-combusted hydrocarbons (smoke)

Possibility of Hazardous Reactions: No

---

**Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

**ACUTE EFFECTS**

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Petroleum distillate	LD50	9 ml/kg	Oral	Rat
Stoddard solvent	LD50	> 5 g/kg	Oral	Rat
Stoddard solvent	LD50	> 3 g/kg	Dermal	Rabbit
Petroleum distillate	LD50	> 5 ml/kg	Dermal	Rabbit

**CHRONIC EFFECTS****Carcinogenicity:**

	<u>Component</u>	<u>Result</u>
OSHA:	Naphthalene	Hazard Communication Carcinogen
IARC:	Naphthalene	2B – Possibly Carcinogenic
NTP:	Naphthalene	Reasonably Anticipated to be a Carcinogen

Mutagenicity: Petroleum Distillate This material has been positive in a mutagenicity study.

---

**Section 12: Ecological Information**

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	No information available
Persistence / Degradability:	No information available
Bioaccumulation / Accumulation:	No information available
Mobility in Environment:	Spills may penetrate the soil causing groundwater contamination. This material may accumulate in sediments.

---

### **Section 13: Disposal Considerations**

Disposal: This product is a RCRA hazardous waste for the ignitability characteristic: D001.  
(See 40 CFR Part 261.20 – 261.33)

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

---

### **Section 14: Transport Information**

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

---

### **Section 15: Regulatory Information**

#### **U.S. Federal**

#### Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

#### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

**Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.**

#### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	No
	Acute Health Hazard	Yes
	Chronic Health Hazard	Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:  
None

**Clean Air Act:**

Section 112 Hazardous Air Pollutants (HAPs): None

**Consumer Product Safety Act General Conformity Certification:** This product was evaluated by CRC Industries, Inc., and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location listed in Section 1 of this MSDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above

**State Regulations****California Safe Drinking Water and Toxic Enforcement Act (Prop 65):**

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: Naphthalene ( < 0.01%)

**State Right to Know:**

New Jersey: 91-20-3, 8052-41-3, 67-63-0  
Pennsylvania: 91-20-3, 8052-41-3, 67-63-0  
Massachusetts: 91-20-3, 8052-41-3, 67-63-0  
Rhode Island : 91-20-3, 8052-41-3, 67-63-0

**Additional Regulatory Information:** This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

---

**Section 16: Other Information**

NFPA:	Health: 2	Flammability: 2	Reactivity: 0	
HMIS:	Health: 2	Flammability: 2	Reactivity: 0	PPE: B

Prepared By: Michelle Rudnick  
CRC #: 690A  
Revision Date: 11/07/2008

Changes since last revision: Section 15: CPSA Certification added

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration		
ACGIH	American Association of Governmental Industrial Hygienists		
NIOSH	National Institute of Occupational Safety & Health		