

This safety data sheet complies with the requirements of: OSHA Hazard Communication Standard (29 CFR 1910.1200)

Product Name: Subaru Certified High Perf. Gear Oil SAE 75W-90, 12 x 1 Qrt. **Product Code:** 30451002-75000C020 Revision Date: 19-Apr-2021

Revision Number: 5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name:

Subaru Certified High Perf. Gear Oil SAE 75W-90, 12 x 1 Qrt.

Other means of identification

Product Code:

30451002-75000C020

Lubricant

1.2 Recommended use of the chemical and restrictions on use

Recommended Use:

1.3 Details of the supplier of the safety data sheet

Manufactured by:

Manufactured for

24 Hour Emergency Phone Number:

Idemitsu Lubricants America Corporation 701 Port Rd., Jeffersonville, IN. 47130

701 Port Rd., Jeffersonville, IN. 47130 Telephone: 1-(812) 284-3300 Business hours: 8am-4:30pm est Email: Ila.sds@idemitsu.com

Subaru of Canada, Inc. 560 Sulffolk Court Mississauga, ON Canada, L5R4J7 Telephone: +1-800-894-4212 Within USA and Canada: 1 800-424-9300 Outside USA and Canada: + 1 703-741-5970 (collect calls accepted)

2. HAZARDS IDENTIFICATION

2.1 Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

2.2 Label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Not applicable

Hazards not otherwise classified (HNOC)

2.3 Other information

Other hazards

May be harmful if swallowed May be harmful in contact with skin Causes mild skin irritation Harmful to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixture

Non-Hazardous Components

| Chemical name | CAS-No | weight-% |
|-------------------------|---------|----------|
| Lubricating Base Stocks | Mixture | 60-70 |
| Synthetic Lubricant | Mixture | 20-30 |

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

4.1 First Aid Measures

| General Advice | If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for medical treatment. |
|----------------|---|
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. |
| Eye Contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists: Get medical advice or attention. |
| Inhalation | Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately. |

| Ingestion | Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty lean forward to reduce the risk of aspiration. If symptoms persist, call a physician. | | |
|--|--|--|--|
| Protection of First-aiders | Use personal protective equipment. Avoid contact with eyes, skin and clothing. | | |
| 4.2 Most important symptoms and | effects, both acute and d | elayed | |
| Symptoms | See Section 11 for additional Toxicological information. | | |
| 4.3 Indication of any immediate me | dical attention and specia | al treatment needed | |
| Notes to Physician | Treat symptomatically. | | |
| 5. FIRE-FIGHTING MEASUR | ES | | |
| Flammable Properties | | NFPA: Class IIIB Combustible Liquid | |
| 5.1 Suitable extinguishing media | | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment | |
| Unsuitable Extinguishing Media: | | Do not use a solid water stream as it may scatter and spread fire. | |
| 5.2 Specific Hazards Arising from the Chemical | | Keep product and empty container away from heat and sources of ignition. | |
| Hazardous combustion products | | During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and are not limited to: Carbon oxides Nitrogen oxides (NOx) Oxides of Phosphorus Sulphur oxides Oxides of Boron | |
| 5.3 Protective Equipment and Prec | autions for Firefighters: | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. | |

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

| Personal precautions | Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of ignition. |
|------------------------------------|--|
| 6.2. Environmental precautions | |
| Environmental Precautions | See section 12 for additional ecological information. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow into any sewer, on the ground or into any body of water. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas. |
| 6.3 Methods and material for conta | inment and cleaning up |

| Methods for Clean-up | Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, |
|----------------------|--|
| | diatomaceus earth, vermiculite) and place in container for disposal according to local / |
| | national regulations (see section 13). |

| Spill Management | |
|------------------|---|
| LARGE SPILLS | Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. |
| WATER SPILLS | Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. |

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

| Handling | Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe vapors, spray, or mist. Use personal protection recommended in the SDS. |
|----------------------|---|
| Safe Handling Advice | Handle in accordance with good industrial hygiene and safety practices. Take precautionary measures against static discharges. |

7.2. Conditions for safe storage, including any incompatibilities

Storage

Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place.

Technical measures/Precautions

Ensure adequate ventilation.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Guidelines

| Chemical name | OSHA PEL | ACGIH TLV | ACGIH OEL (STEL) | NIOSHT REL TWA | ILA IHG | ILA ROEG | ILA Internal Exposure Limit |
|-------------------|-----------------------------|-----------------------------|---------------------|--|---------|----------|-----------------------------------|
| Oil mist, mineral | TWA: 5 mg/m ³ | TWA: 5 mg/m ³ | | TWA 5 mg/m ³ ST 10 mg/m ³ | | | |

8.2 Exposure controls

Appropriate engineering controls Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Eye/face protection Safety glasses equipped with side shields are recommended as minimum protection in

| | industrial settings. |
|--------------------------------|---|
| Skin protection | Choose the appropriate protective clothing and gloves based on the tasks being performed to avoid exposed skin surfaces. Glove Type: Neoprene, Nitriles |
| Respiratory protection | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. |
| General Hygiene Considerations | When using, do not eat, drink or smoke. Remove and wash contaminated clothing before re-use. Clean equipment, work area and clothing regularly. |

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| Appearance Physical state Odor Odor Threshold pH Melting point / melting range Boiling point / boiling range Flash Point Evaporation Rate Flammability Limit in Air Explosion Limits Vapor pressure @20 °C (kPa) Vapor density Density | Yellow / Clear Liquid Mild No information available Not applicable No information available 220 °C / 428 °F COC ASTM D92 No information available No information available No information available No information available No information available No information available |
|---|--|
| Density | 0.85 g/cm ³ @15°C |
| Solubility(ies) | No information available |
| Partition coefficient | No information available |
| Autoignition Temperature | No information available |
| Decomposing Temperature | No information available |
| Kinematic viscosity | @ 40C = 98.54 cSt; @ 100C = 14.94 cSt |

9.2. Other information

DMSO extract by IP346

Less than 3.0 wt% (mineral oil component only)

10. STABILITY AND REACTIVITY

| 10.1. Reactivity | |
|--|--|
| Reactivity | The product is chemically stable. |
| 10.2. Chemical stability | |
| Chemical Stability | Stable under recommended storage conditions. |
| 10.3. Possibility of hazardous reactions | |
| Possibility of Hazardous Reactions | None under normal processing. |
| 10.4. Conditions to avoid | |
| Conditions to Avoid | Heat, flames and sparks. |
| | |

10.5. Incompatible materials

Incompatible Materials

10.6. Hazardous decomposition products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

Strong oxidizing agents

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

| Inhalation | May cause irritation of respiratory tract. |
|--------------|--|
| Eye contact | May cause slight irritation. |
| Skin Contact | May cause skin irritation and/or dermatitis. |
| Ingestion | May be harmful if swallowed. |

11.2 Information on toxicological effects

No information available

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

| Skin corrosion/irritation | Not classified. |
|--------------------------------------|--|
| Serious eye damage/eye irritation | Not classified. |
| Sensitization | Not classified. |
| Mutagenic effects | Not classified. |
| Reproductive Toxicity | Not classified |
| STOT - single exposure | Not classified. |
| STOT - repeated exposure | Not classified |
| Aspiration hazard | Not classified. |
| 11.4 Carcinogenicity | |
| Carcinogenicity: | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH. |
| Legend: | NTP (National Toxicology Program), IARC (International Agency for Research on Cancer), OSHA (Occupational Safety and Health Administration of the US Department of Labor), ACGIH (American Conference of Governmental Industrial Hygienists) |

11.5 Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

| Product Information (I | Estimated): | | |
|------------------------|-------------|--|--|
| ATEmix (oral) | >5000 mg/kg | | |

| ATEmix (dermal) | >5000 mg/kg |
|-------------------------------|-------------|
| ATEmix (inhalation-dust/mist) | >5 mg/l |

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecotoxicity effects Harmful to aquatic life. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

| 12.2 Persistence and degradability | No information available. |
|--------------------------------------|---------------------------|
| 12.3. Bioaccumulative potential | No information available. |
| 12.4 Mobility in Environmental Media | No information available. |
| 12.5 Other adverse effects: | No information available. |
| PBT and vPvB assessment | No information available |

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

| Waste Disposal Method | This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, if the material is processed or otherwise altered. Consult 40 CFR 261 to determine wheth the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements. | |
|------------------------|--|--|
| Contaminated packaging | Dispose of in accordance with local regulations. | |
| 14.TRANSPORT INFORMAT | ION | |
| DOT | Not regulated | |
| IATA | Not regulated | |
| IMDG | Not regulated | |

15. REGULATORY INFORMATION

International Inventories

| TSCA | All ingredients are on the inventory or exempt from listing |
|------|---|
| | |

| DSL/NDSL | There are ingredients listed on the NDSL Inventory List | | | |
|---|---|------|------------|----------|
| Chemical name | | NDSL | CAS-No | weight-% |
| 2-Mercapto-5-tert-nonyldithio-1,3,4-thiadiazo | ole (Accession | Х | 97503-12-3 | <0.1 |
| # 54785) listed on TSCA confiden | tially | | | |
| ENCS | All ingredients are on the inventory or exempt from listing | | | |
| IECSC | All ingredients are on the inventory or exempt from listing | | | |
| KECL | All ingredients are on the inventory or exempt from listing | | | |
| PICCS | All ingredients are on the inventory or exempt from listing | | | |
| AICS | All ingredients are on the inventory or exempt from listing | | | |
| NZIoC | All ingredients are on the inventory or exempt from listing | | | |

| USA | | |
|---------------------|--|--|
| | | |
| Federal Regulations | | |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazardous Categorization

| Acute health hazard | No |
|-----------------------------------|----|
| Chronic Health Hazard | No |
| Fire hazard | No |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

| Chemical name | CAS-No | weight-% | RQ | TPQ |
|-----------------|----------|-----------|--|--------------|
| n-Butyl alcohol | 71-36-3 | <0.1 | RQ 5000lb final RQ RQ 2270kg final RQ | |
| Ethyl acrylate | 140-88-5 | <0.001 | RQ 1000lb final RQ RQ 454kg final RQ | |
| 1,4-Dioxane | 123-91-1 | <0.000001 | RQ 100lb final RQ RQ 45.4kg final RQ | |
| Ethylene oxide | 75-21-8 | <0.000001 | RQ 10lb final RQ RQ 4.54kg final RQ | 1000 lb TPQ |
| Propylene oxide | 75-56-9 | <0.000001 | RQ 100lb final RQ RQ 45.4kg final RQ | 10000 lb TPQ |

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

| Chemical name | CAS-No | weight-% | HAPS data |
|-----------------|----------|----------|-----------|
| Ethyl acrylate | 140-88-5 | <0.001 | Х |
| 1,4-Dioxane | 123-91-1 | <0.00001 | Х |
| Ethylene oxide | 75-21-8 | <0.00001 | Х |
| Propylene oxide | 75-56-9 | <0.00001 | Х |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| | Chemical name | CAS-No | weight-% | U.S CWA (Clean Water |
|--|---------------|--------|----------|----------------------|
|--|---------------|--------|----------|----------------------|

| | | | Act) |
|-----------------|---------|----------|------|
| Propylene oxide | 75-56-9 | <0.00001 | Х |

State Regulations

California Proposition 65

Label:

WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov


| Chemical name | CAS-No | weight-% | California Prop. 65 | Maximum Allowable Dose for Reproductive Toxicity (MADLS) | Safe Harbor Limits for Cancer-causing Chemicals (NSRLs) |
|-----------------|----------|-----------|--|--|---|
| Ethyl acrylate | 140-88-5 | <0.001 | Carcinogen | | |
| 1,4-Dioxane | 123-91-1 | <0.00001 | Carcinogen | | 30 µg/day |
| Ethylene oxide | 75-21-8 | <0.000001 | Carcinogen Developmental Female Reproductive Male Reproductive | 20µg/day | 2 μg/day |
| Propylene oxide | 75-56-9 | <0.000001 | Carcinogen | | |

State Right-to-Know

| Chemical name | CAS-No | weight-% | New Jersey |
|--|------------|----------|------------|
| Distillates, petroleum, hydrotreated heavy paraffinic | 64742-54-7 | 5-10 | Х |
| Distillates (petroleum), solvent-refined heavy paraffinic | 64741-88-4 | <1 | Х |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-65-0 | <1 | Х |
| Petroleum distillates, hydrotreated light paraffinic | 64742-55-8 | <1 | Х |
| Di(2-ethylhexyl)phosphoric acid | 298-07-7 | <1 | Х |
| Distillates (Petroleum), solvent-dewaxed light paraffinic | 64742-56-9 | <1 | Х |

New Jersey Worker and Community Right-to-Know Act:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Lubricating Oil)



| Revision Date: | 19-Apr-2021 |
|-------------------|--|
| Revision Summary: | Section 1: Identification of the hazardous chemical and of the supplier Section 15: REGULATORY INFORMATION |

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet