#### SDS Revision Date (mm/dd/yyyy): 03/04/2019

# SAFETY DATA SHEET

# SECTION 1. IDENTIFICATION

Product identifier used on the label

: Lubricity Plus Fuel Power

Other means of identification: US Product Codes: 00105, 90105, 00112P, 00113, 90110, 00110

Canada Product Codes: 00223, 90223, 90401, 00401

Refer to manufacturer

Recommended use of the chemical and restrictions on use

: Diesel fuel treatment. No restrictions on use known.

Chemical family : Mixture.

Name, address, and telephone number of Name, address, and telephone number of

the manufacturer: the supplier:

FPPF Chemical Company, Inc.

117 West Tupper Street Buffalo, NY, USA

14201

Manufacturer's Telephone # : 1-800-735-3773

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887

(Outside U.S.).

#### SECTION 2. HAZARDS IDENTIFICATION

#### Classification of the chemical

Clear to slightly hazy amber liquid. Solvent odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification

Flammable Liquids - Category 3

Acute Toxicity, dermal - Category 4

Acute Toxicity, inhalation - Category 3 (vapor)

Skin Irritation - Category 2

Eve damage/irritation -Category 2A

Aspiration Toxicity - Category 1

Reproductive Toxicity-Category 1

Carcinogenicity- Category 2

Specific target organ ooxicity, single exposure - Category 3 (narcotic effects)

Specific target organ toxicity, single exposure - Category 3 (respiratory)

Specific Target organ toxicity, repeated exposure- Category 1

#### Label elements

Hazard pictogram(s)









Signal Word

DANGER!

#### Hazard statement(s)

Flammable liquid and vapor.

Harmful in contact with skin.

Toxic if inhaled.

Causes skin irritation.

Causes serious eve irritation.

May cause respiratory irritation.

May cause drowsiness and dizziness.

May be fatal if swallowed and enters airways.

Suspected of causing cancer.

Suspected of damaging the unborn child.

Causes damage to organs through prolonged or repeated exposure.

#### Precautionary statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, sparks and open flame - No smoking.

Ground and bond container and receiving equipment.

Use explosion-proof electrical and ventilating equipment.

Use non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist or vapor.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/clothing and eye/face protection.

Wash hands and face thoroughly after handling.

If exposed or concerned: Call a POISON CENTER or doctor/physician.

Get medical advice/attention if you feel unwell.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs, get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use water fog, dry chemical, CO2 or 'alcohol' foam to extinguish.

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification: May be sensitive to static discharge. Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION. Section 12.

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	Common name and synonyms	CAS#	Concentration (% by weight)	
stoddard solvent	Mineral spirits White spirit	8052-41-3	45.0 - 70.0	
2-Butoxy ethanol	Ethylene Glycol Monobutyl Ether EGBE	111-76-2	10.0 - 30.0	
Light aromatic solvent naphtha	Aromatic solvent naphtha Solvent Naphtha (Petroleum) Light Aromatic	64742-95-6	5.0 - 10.0	
2-Ethylhexanol	2-Ethylhexyl Alcohol	104-76-7	3.0 - 7.0	

2-Ethylhexyl nitrate	Ethylhexyl nitrate Nitric acid, 2-ethylhexyl ester	27247-96-7	1.0 - 5.0
oleic acid	Oleinic acid; 9-Octadecenoic acid; Elaic acid	112-80-1	1.0 - 5.0
Heavy aromatic solvent naphtha	Aromatic solvent naphtha Heavy Aromatic Naphtha	64742-94-5	1.0 - 5.0
1,2,4-Trimethylbenzene	Pseudocumene	95-63-6	0.5 - 1.5
1,3,5-Trimethyl benzene	Trimethylbenzol Mesitylene	108-67-8	0.5 - 1.5
Propylbenzene	N-Propylbenze Isocumene 1-Propylbenzene	103-65-1	0.1 - 1.0
Naphthalene	Moth balls Moth flakes Tar camphor	91-20-3	0.1 - 1.0
Xylene (mixed isomers)	Dimethylbenzene Methyltoluene Xylol	1330-20-7	0.1 - 1.0
Cumeme	Isopropyl benzene Cumol 2-Phenyl propane	98-82-8	0.1 - 1.0
1,2,3-Trimethylbenzene	Hemellitol Hemimellitene	526-73-8	0.1 - 1.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

# SECTION 4. FIRST-AID MEASURES

# Description of first aid measures

Ingestion : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT

induce vomiting. Aspiration hazard. Never give anything by mouth to an unconscious

person. If vomiting occurs spontaneously, keep victim's head lowered

(forward) to reduce the risk of aspiration.

Inhalation : If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a

POISON CENTRE or doctor/physician if you feel unwell. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical

personnel only.

Skin contact : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower. Call a POISON CENTER or doctor/physician if you feel unwell. If skin

irritation occurs, get medical advice/attention.

Eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: get medical

advice/attention.

#### Most important symptoms and effects, both acute and delayed

: IF exposed or concerned: Get medical attention/advice.

Harmful in contact with skin. May be absorbed through the skin, producing symptoms similar to ingestion or inhalation.

Toxic if inhaled. Symptoms may include coughing, choking and wheezing. May cause respiratory impairment and lung damage.

May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties.

May cause drowsiness or dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.

Causes skin irritation. Symptoms may include redness, itching and swelling. Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing.

Suspected of causing cancer. Symptoms may include persistent coughing, shortness of breath, coughing up blood and wheezing.

Suspected of damaging the unborn child. Symptoms in offspring may include reduced fetal weight, behavioral effects, delayed skeletal formation and hearing loss. Causes damage to organs through prolonged or repeated exposure.

Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights. Chronic overexposure to 2-butoxyethanol may cause liver, kidney and blood damage, based on animal data. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

#### Indication of any immediate medical attention and special treatment needed

: Immediate medical attention is required. Provide general supportive measures and treat symptomatically. Show this safety data sheet to the doctor in attendance.

# SECTION 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

Suitable extinguishing media

: Dry chemical, foam, carbon dioxide and water fog.

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.

#### Special hazards arising from the substance or mixture / Conditions of flammability

: Flammable liquid and vapor. Keep away from heat, sparks and open flames. This product will accumulate static charge by flow, splashing or agitation. After prolonged storage, may release explosive peroxides in the presence of air. Vapors may travel considerable distance to a source of ignition and flash back. Vapours may be heavier than air and may collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

# Flammability classification (OSHA 29 CFR 1910.106)

: Flammable Liquids - Category 3

#### **Hazardous combustion products**

 Carbon oxides. Nitrogen oxides. Reactive hydrocarbons. Aldehydes. Other irritating fumes and smoke.

# Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

#### Special fire-fighting procedures

: Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply or any natural waterway. Dike for water control.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

: Evacuate personnel to safe areas. Keep all other personnel upwind and away from the spill/release. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

#### **Environmental precautions**

Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

## Methods and material for containment and cleaning up

: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

#### Special spill response procedures

In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802). US CERCLA Reportable quantity (RQ):

Naphthalene (100 lbs / 45.4 kg); Xylene (100 lbs / 45.4 kg); Cumene (5000 lbs / 2270 kg).

#### SECTION 7. HANDLING AND STORAGE

#### Precautions for safe handling

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks and open flame - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Do not breathe mist or vapor. Do not ingest. Do not eat, drink, smoke or use cosmetics while working with this product. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.

#### Conditions for safe storage

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up. Store away from incompatibles and out of direct sunlight. After prolonged storage, may release explosive peroxides in the presence of air. Direct sunlight or heat may accelerate the release of peroxides. Rate of peroxide formation is not known. Take measures to prevent the build up of electrostatic charge. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

#### Incompatible materials

: Strong oxidizing agents; Acids; Perchloric acid; Alkalies; Bases.

#### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name	ACGIH	<u>TLV</u>	OSHA F	PEL
	<u>TWA</u>	STEL	<u>PEL</u>	<u>STEL</u>
stoddard solvent	100 ppm	N/Av	500 ppm (2900 mg/m³)	N/Av
2-Butoxy ethanol	20 ppm	N/Av	50 ppm (skin)	N/Av
Light aromatic solvent naphtha	N/Av	N/Av	N/Av	N/Av
2-Ethylhexanol	N/Av	N/Av	N/Av	N/Av
2-Ethylhexyl nitrate	N/Av	N/Av	N/Av	N/Av
oleic acid	N/Av	N/Av	N/Av	N/Av
Heavy aromatic solvent naphtha	N/Av	N/Av	500 ppm (as petroleum distillates, naphtha)	N/Av
1,2,4-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
1,3,5-Trimethyl benzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
Propylbenzene	N/Av	N/Av	N/Av	N/Av
Naphthalene	10 ppm (skin)	N/Av	10 ppm ; 50 mg/m³	15ppm; 75mg/m
Xylene (mixed isomers)	100 ppm	150 ppm	100 ppm (435 mg/m³)	N/Av
Cumeme	50 ppm	N/Av	50 ppm ; 245 mg/m³ (Skin)	N/Av
1,2,3-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	ppm (trimethylbenzene) (final rule limit)	N/Av

## **Exposure controls**

Ventilation and engineering measures:

Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Wear protective gloves/clothing. Where extensive exposure to product is possible, use Skin protection: resistant coveralls, apron and boots to prevent contact. The suitability for a specific

workplace should be discussed with the producers of the protective gloves.

: Wear eye/face protection. Chemical splash goggles are recommended. A full face

Eye / face protection shield may also be necessary.

Other protective equipment, such as an eyewash station and safety shower, may be Other protective equipment : required depending on exposure and on workplace standards. Other equipment may

be required depending on workplace standards.

#### General hygiene considerations

Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance**: Clear to slightly hazy amber liquid.

Odour : Solvent odor.

Odour threshold : N/Av
pH : N/Av
Melting Point/Freezing point : N/Av
Initial boiling point and boiling range

: >149°C / >300°F

Flash point : 38.3°C / 101°F
Flashpoint (Method) : Tag closed cup

Evaporation rate (BuAe = 1) : N/Av Flammability (solid, gas) : N/Ap Lower flammable limit (% by vol.)

: N/Av

Upper flammable limit (% by vol.)

: N/Av

Oxidizing properties : None known.

**Explosive properties**: N/Av

Vapour pressure : <3mm Hg @ 20°C

Vapour density : >1 Relative density / Specific gravity

: 0.83

Solubility in water : Partially soluble.

Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Av Decomposition temperature : N/Av Viscosity : N/Av

Volatiles (% by weight) : 87%(approximately)

**Volatile organic Compounds (VOC's)** 

: N/Av

Absolute pressure of container

: N/Ap

Flame projection length : N/Ap Other physical/chemical comments

: None reported by the manufacturer.

#### SECTION 10. STABILITY AND REACTIVITY

**Reactivity**: Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

Hazardous polymerization will not occur. May be sensitive to static discharge. May form explosive peroxides during prolonged exposure to air and heat. Rate of peroxide

formation is not known.

Conditions to avoid : Keep away from heat, sparks and flame. Keep away from direct sunlight. Ensure

adequate ventilation, especially in confined areas. Take precautionary measures

against static discharge. Avoid contact with incompatible materials.

Incompatible materials : Strong oxidizing agents; Acids; Bases; Perchloric acid; Alkalies

#### **Hazardous decomposition products**

: None reported by the manufacturer. Refer also to hazardous combustion products, Section 5.

#### SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption

: YES

## **Potential Health Effects:**

#### Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

Toxic if inhaled. Inhalation may cause respiratory irritation and central nervous system depression. Symptoms include: Upper respiratory irritation, coughing, sneezing, staggering gait, giddiness, drowziness, slurred speech, nausea, and possible nervous system depression.

Sign and symptoms ingestion

: Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. Causes symptoms similar to those listed for inhalation. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing.

Sign and symptoms skin

: Harmful in contact with skin. May be absorbed through the skin, producing symptoms similar to ingestion or inhalation.

Causes skin irritation. Symptoms include: Dryness, itching, cracking, burning,

redness and swelling.

Sign and symptoms eyes

Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

#### **Potential Chronic Health Effects**

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Chronic overexposure to 2-butoxyethanol may cause liver, kidney and blood damage.

# Mutagenicity Carcinogenicity

: Not expected to be mutagenic in humans.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification: Carcinogenicity- Category 2. Suspected of causing cancer.

Contains Naphthalene. Naphthalene is classified as carcinogenic by IARC (Group 2B) and NTP (Group 2 - Reasonably anticipated).

Contains Cumene. Cumene is classified as possibly carcinogenic by IARC (Group 2B).

#### Reproductive effects & Teratogenicity

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification: Reproductive Toxicity - Category 1B Suspected of damaging the unborn child. Developmental

Contains Xylene (mixed isomers) Xylene may cause fetotoxic effects (e.g. reduced fetal weight, delayed ossification, behavioral effects) at doses which are not maternally toxic, based on animal data.

Sensitization to material

: Not expected to be a skin or respiratory sensitizer.

Page 9 of 18 SDS Revision Date (mm/dd/yyyy): 03/04/2019

# SAFETY DATA SHEET

Specific target organ effects: Eyes, skin, respiratory system, digestive system, central nervous system, blood

system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products

Regulations) (WHMIS 2015).

Classification:

Specific target organ toxicity, single exposure Category 3 May cause drowsiness and

dizziness. May cause respiratory irritation.

Specific Target organ toxicity, repeated exposure- Category 1 Causes damage to organs through prolonged or repeated exposure.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials Toxicological data

: None reported by the manufacturer.

: The calculated ATE values for this mixture are:

ATE oral = 246 mg/kg ATE dermal = 1430 mg/kg

ATE inhalation (vapours) =7.99 mg/L/4H ATE inhalation (mists) = 25.6 mg/L/4H

See below for individual ingredient acute toxicity data.

	LC <sub>50</sub> (4hr)	LD <sub>50</sub>			
Chemical name	inh, rat	(Oral, rat)	(Rabbit, dermal)		
stoddard solvent	> 5.5 mg/L (vapour)	> 5000 mg/kg	> 3000 mg/kg		
2-Butoxy ethanol	450 ppm (2.175 mg/L)	530 mg/kg	400 - 500 mg/kg		
Light aromatic solvent naphtha	>17.7mg/L/4H (vapour)	8400 mg/kg	>3160 mg/kg		
2-Ethylhexanol	≥1.2 - <5.3 mg/L	2052mg/kg	No information available.		
2-Ethylhexyl nitrate	> 14 mg/L	>10mg/L (>9600mg/kg)	>5 mL/kg (>4800mg/kg)		
oleic acid	N/Av	>19200 mg/kg	>3000mg/kg guinea pig		
Heavy aromatic solvent naphtha	> 17.1 mg/L/4 hours	> 6000 mg/kg	> 3160 mg/kg		
1,2,4-Trimethylbenzene	18 mg/L	5000 mg/kg	> 3160 mg/kg		
1,3,5-Trimethyl benzene	24 mg/L	23 000 mg/kg	>3160mg/kg		
Propylbenzene	159.25mg/L	6040 mg/kg	N/Av		
Naphthalene	No information available.	490 mg/kg	>20,000 mg/kg		
Xylene (mixed isomers)	6350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg		
Cumeme	8000 ppm; 39 mg/L	2260 mg/kg	10 627 mg/kg		
1,2,3-Trimethylbenzene	18 - 24mg/L/4H (based on similar substances)	4472mg/kg	>3160mg/kg		

#### Other important toxicological hazards

: None known or reported by the manufacturer.

# SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity** : No data is available on the product itself.

See the following tables for individual ingredient ecotoxicity data.

# Ecotoxicity data:

		Toxicity to Fish				
<u>Ingredients</u>	CAS No	LC50 / 96h	NOEC / 21 day	M Factor		
stoddard solvent	8052-41-3	2.1 - 4.2 mg/L (Bluegill sunfish)	N/Av	None.		
2-Butoxy ethanol	111-76-2	1490 mg/L (Lepomis macrocrhius)	>100mg/L (Zebra fish)	none		
Light aromatic solvent naphtha	64742-95-6	9.22 mg/L (Rainbow trout)	N/Av	None.		
2-Ethylhexanol	104-76-7	2 mg/L (Zebra fish)	N/Av	None.		
2-Ethylhexyl nitrate	27247-96-7	2 mg/L (Zebra fish)	N/Av	None.		
oleic acid	112-80-1	205 mg/L (Fathead minnow)	N/Av	None.		
Heavy aromatic solvent naphtha	64742-94-5	3.6 mg/L (Rainbow trout)	N/Av	none		
1,2,4-Trimethylbenzene	95-63-6	7.19 - 8.28 mg/L (Fathead minnow)	N/Av	None.		
1,3,5-Trimethyl benzene	108-67-8	12.52 mg/L (Goldfish)	N/Av	None.		
Propylbenzene	103-65-1	1.55mg/L (Rainbow trout)	N/Av	None.		
Naphthalene	91-20-3	0.96 mg/L (pink salmon)	0.12mg/L (40 days) (pink salmon)	none		
Xylene (mixed isomers)	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.		
Cumeme	98-82-8	4.5mg/L (Rainbow trout)	0.38mg/L QSAR	None.		
1,2,3-Trimethylbenzene	526-73-8	7.8mg/L (Species not specified)	N/Av	None.		

<u>Ingredients</u>	CAS No	Toxic	Toxicity to Daphnia				
		EC50 / 48h	NOEC / 21 day	M Factor None.			
stoddard solvent	8052-41-3	0.42 - 2.3 mg/L (Daphnia magna) (Closed systems - low end; Open systems - high end)	0.1 - 0.37 mg/L				
2-Butoxy ethanol	111-76-2	835mg/L (Daphnia magna)	100mg/L (Daphnia magna)	none			
Light aromatic solvent naphtha	64742-95-6	6.16 mg/L (Daphnia magna)	N/Av	None.			
2-Ethylhexanol	104-76-7	>12.6mg/L (Daphnia magna)	N/Av	None.			
2-Ethylhexyl nitrate	27247-96-7	> 12.6 mg/L [Daphnia magna (Water flea)]	N/Av	None.			
oleic acid	112-80-1	N/Av	N/Av	None.			
Heavy aromatic solvent naphtha	64742-94-5	1.1 mg/L Water flea	N/Av	none			
1,2,4-Trimethylbenzene	95-63-6	6.14 mg/L (Daphnia magna)	N/Av	None.			
1,3,5-Trimethyl benzene	108-67-8	6 mg/L (Daphnia magna)	0.4mg/L	None.			
Propylbenzene	103-65-1	2mg/L/24hr	N/Av	None.			
Naphthalene	91-20-3	3.4 mg/L/ Water flea	0.6mg/L	none			
Xylene (mixed isomers)	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.			
Cumeme	98-82-8	2.14 mg/L (Daphnia magna)	0.35mg/L Nor				
1,2,3-Trimethylbenzene	526-73-8	2.7mg/L Water flea	N/Av	None.			

<u>Ingredients</u>	CAS No	То	Toxicity to Algae			
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor		
stoddard solvent	8052-41-3	0.58 - 1.2 mg/L/72hr (Green algae) (Closed systems - low end; Open systems - high end)	0.16 mg/L/72hr	None.		
2-Butoxy ethanol	111-76-2	911mg/L/72hr	286mg/L/72hr	none		
Light aromatic solvent naphtha	64742-95-6	N/Av	N/Av	N/Av		
2-Ethylhexanol	104-76-7	1.57mg/L/72hr (Green algae)	12.6mg/L/72hr	None.		
2-Ethylhexyl nitrate	27247-96-7	1.57 mg/L/72hr (Green algae)	12.6mg/L/72hr	None.		
oleic acid	112-80-1	N/Av	N/Av	None.		
Heavy aromatic solvent naphtha	64742-94-5	7.2 mg/L/72 hours (Green algae)	0.22 mg/L/72 hours (Green algae)	none		
1,2,4-Trimethylbenzene	95-63-6	N/Av	N/Av	None.		
1,3,5-Trimethyl benzene	108-67-8	3.191mg/L QSAR	N/Av	None.		
Propylbenzene	103-65-1	1.8mg/L/72hr (Green algae)	N/Av	None.		
Naphthalene	91-20-3	0.4mg/L/72hr (Marine diatom)	N/Av	none		
Xylene (mixed isomers)	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.		
Cumeme	98-82-8	1.29mg/L/72hr (Green algae)	0.73mg/L No			
1,2,3-Trimethylbenzene	526-73-8	5.7mg/L	N/Av	None.		

# Persistence and degradability

: No data is available on the product itself. The following ingredients are considered to

be readily biodegradable: 2-butoxyethanol, 2-Ethylhexanol

**Bioaccumulation potential**: No data is available on the product itself.

See the following data for ingredient information.

# SDS Revision Date (mm/dd/yyyy): 03/04/2019

# SAFETY DATA SHEET

<u>Components</u>	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Light aromatic solvent naphtha (CAS 64742-95-6)	2.1 - 6(calculated)	10 - 2500
2-Butoxy ethanol (CAS 111-76-2)	0.81 at 25 °C	0.97
Naphthalene (CAS 91-20-3)	3.7	30 - 430 species: fish
1,2,4-Trimethylbenzene (CAS 95-63-6)	3.78	31 - 275
1,3,5-Trimethyl benzene (CAS 108-67-8)	3.6 - 3.93	23 - 328
Xylene (mixed isomers) (CAS 1330-20-7)	3.12 - 3.2	50 - 58
Cumeme (CAS 98-82-8)	3.55 at 23 °C	224
oleic acid (CAS 112-80-1)	7.64	10 (calculated)
Propylbenzene (CAS 103-65-1)	3.68	138 (estimated)
1,2,3-Trimethylbenzene (CAS 526-73-8)	3.76	133 - 259
stoddard solvent (CAS 8052-41-3)	3.16 - 7.06	No information available.
Heavy aromatic solvent naphtha (CAS 64742-94-5)	2.9 - 6.1	No information available.
2-Ethylhexyl nitrate (CAS 27247-96-7)	5.24	No information available.
2-Ethylhexanol (CAS 104-76-7)	2.9	30

Mobility in soil

: No data is available on the product itself.

#### Other Adverse Environmental effects

: The ecological characteristics of this product have not been fully investigated. Contains material that may be harmful in the environment. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

# SECTION 13. DISPOSAL CONSIDERATIONS

**Handling for Disposal** 

: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

**Methods of Disposal** 

: Dispose in accordance with all applicable federal, state, provincial and local regulations.

**RCRA** 

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

# SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1993	FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Aromatic naphtha)	3	III	3
49CFR/DOT Additional information	Combustible liq	ay be reclassed as a 'Combustible liquid', when shipping buids may be shipped as non-hazardous material when shi ). Refer to 49 CFR Section 173.150. Seets the criteria for an environmentally hazardous material	pped in non-bu	lk container	s (450 L / 119
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Aromatic naphtha)	3	III	3
TDG Additional information	the requiremen	ay be shipped as non-regulated material when in small me ts of TDG section 1.33 are met. eets the criteria for an environmentally hazardous material		`	<i>7.</i> 1

Special precautions for user : Appropriate advice on safety must accompany the package. Keep away from heat,

sparks and open flame - No smoking.

**Environmental hazards** : This product meets the criteria for an environmentally hazardous material according to

the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

# SECTION 15 - REGULATORY INFORMATION

# **US Federal Information:**

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	0.4.0.#	TSCA	CERCLA Reportable	SARA TITLE III: Sec. 302, Extremely	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical		
	CAS#	Inventory	Quantity(RQ) (40 CFR 117.302):	Hazardous Substance, 40 CFR 355:	Toxic Chemical	de minimus Concentration	
stoddard solvent	8052-41-3	Yes	None.	None.	No	N/Ap	
2-Butoxy ethanol	111-76-2	Yes	N/Ap	N/Av	No	N/Ap	
Light aromatic solvent naphtha	64742-95-6	Yes	N/Ap	N/Ap	No	N/Ap	
2-Ethylhexanol	104-76-7	Yes	N/Ap	N/Av	No	N/Ap	
2-Ethylhexyl nitrate	27247-96-7 Yes N/Ap		N/Av	No	N/Ap		
oleic acid	112-80-1	Yes	N/Ap	N/Av	No	N/Ap	
Heavy aromatic solvent naphtha	64742-94-5	Yes	N/Ap	N/Av	No	N/Ap	
1,2,4-Trimethylbenzene	95-63-6	Yes	N/Ap	N/Ap	Yes	1%	
1,3,5-Trimethyl benzene	108-67-8	Yes	N/Ap	N/Av	No	N/Ap	
Propylbenzene	103-65-1	Yes	N/Ap	N/Av	No	N/Ap	
Naphthalene	91-20-3	Yes	100 lb/ 45.4 kg	N/Av	Yes	0.1%	
Xylene (mixed isomers)	1330-20-7	Yes	100 lb/ 45.4 kg	None.	Yes	1%	
Cumeme	98-82-8	Yes	5000 lb/ 2270 kg	N/Ap	Yes	1%	
1,2,3-Trimethylbenzene	526-73-8	Yes	N/Ap	N/Av	No	N/Ap	

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Physical hazards (Flammable) Health hazards (Carcinogenicity; Specific target organ toxicity, single exposure; Specific target organ toxicity, repeated exposure; Reproductive toxicity; Acute toxicity; Aspiration hazard; Eye irritation; Skin irritation). Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

### **US State Right to Know Laws:**

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS#	Californ	ia Proposition 65		State "Right to Know" Lists					
	CAS#	Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI	
stoddard solvent	8052-41-3	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes	
2-Butoxy ethanol	111-76-2	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes	
Light aromatic solvent naphtha	64742-95-6	No	Not listed	No	No	No	No	No	No	
2-Ethylhexanol	104-76-7	No	Not listed	No	Yes	No	No	Yes	No	
2-Ethylhexyl nitrate	27247-96-7	No	Not listed	No	No	No	No	No	No	
oleic acid	112-80-1	No	Not listed	No	No	No	No	Yes	No	
Heavy aromatic solvent naphtha	64742-94-5	No	Not listed	No	No	No	No	No	No	
1,2,4-Trimethylbenzene	95-63-6	No	Not listed	No	Yes	Yes	Yes	Yes	No	
1,3,5-Trimethyl benzene	108-67-8	No	Not listed	Yes	Yes	No	No	No	No	
Propylbenzene	103-65-1	No	Not listed	No	Yes	No	Yes	Yes	No	
Naphthalene	91-20-3	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes	
Xylene (mixed isomers)	1330-20-7	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes	
Cumeme	98-82-8	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes	
1,2,3-Trimethylbenzene	526-73-8	No	Not listed	No	No	No	No	No	No	

# **Canadian Information:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS Classification: See Section 2.

## **International Information:**

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
stoddard solvent	8052-41-3	232-489-3	Present	Present	(9)-1702	KE-32199	Present	HSR001498
2-Butoxy ethanol	111-76-2	203-905-0	Present	Present	(7)-97; (2)-407	KE-04134	Present	HSR001154
Light aromatic solvent naphtha	64742-95-6	265-199-0	Present	Present	(9)-1698	KE-31662	Present	May be used as a single component chemical under an appropriate group standard.
2-Ethylhexanol	104-76-7	203-234-3	Present	Present	(2)-217	KE-13766	Present	HSR001386
2-Ethylhexyl nitrate	27247-96-7	248-363-6	Present	Present	(2)-3598	KE-13803	Present	May be used as a single component chemical under an appropriate group standard.
oleic acid	112-80-1	204-007-1	Present	Present	(2)-975; (2)-609	KE-26450	Present	HSR003153
Heavy aromatic solvent naphtha	64742-94-5	265-198-5	Present	Present	(3)-7	KE-31656	Present	May be used as a single component chemical under an appropriate group standard
1,2,4-Trimethylbenzene	95-63-6	202-436-9	Present	Present	(3)-7; (3)-3427	KE-34410	Present	HSR001382
1,3,5-Trimethyl benzene	108-67-8	203-604-4	Present	Present	(3)-7; (3)-3427	KE-34411	Present	HSR001229
Propylbenzene	103-65-1	203-132-9	Present	Present	(3)-21	KE-29781	Present	HSR005222
Naphthalene	91-20-3	202-049-5	Present	Present	(4)-311	KE-25545	Present	HSR001287
Xylene (mixed isomers)	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
Cumeme	98-82-8	202-704-5	Present	Present	(3)-32; (3)-22	KE-23957	Present	HSR001184
1,2,3-Trimethylbenzene	526-73-8	208-394-8	Present	Present	(3)-7; (3)-3427	KE-34409	Present	HSR004095

# **SECTION 16. OTHER INFORMATION**

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists

ATE: Acute Toxicity Estimate

AICS: Australian Inventory of Chemical Substances

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

of 1980

CFR: Code of Federal Regulations CNS: Central Nervous System CSA: Canadian Standards Association DOT: Department of Transportation EC50: Effective Concentration 50%

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances

EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

Inh: Inhalation

IMDG: International Maritime Dangerous Goods KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration

LD: Lethal Dose

SDS Revision Date (mm/dd/yyyy): 03/04/2019

#### SAFETY DATA SHEET

MA: Massachusetts MN: Minnesota

MSHA: Mine Safety and Health Administration

N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration NTP: National Toxicology Program

NJ: New Jersey

NOEC: No observable effect concentration

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RCRA: Resource Conservation and Recovery Act

RI: Rhode Island

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TPQ: Threshold Planning Quantity TSCA: Toxic Substance Control Act TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents &

Biological Exposure Indices for 2018.

2. International Agency for Research on Cancer Monographs, searched 2018.

3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2018

(Chempendium, HSDB and RTECs).

Material Safety Data Sheets from manufacturer.
 US EPA Title III List of Lists - March 2015 version.

6. California Proposition 65 List - November 23, 2018 version.

7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal,

2018.

Preparation Date (mm/dd/yyyy)

: 07/02/2015

Reviewed Date SDS (dd/mm/yyyy)

: 04/03/2019

Revision No. : 2

Revision Information : (M)SDS sections updated : 2. HAZARDS IDENTIFICATION 4. FIRST AID MEASURES

7. HANDLING AND STORAGE 11. TOXICOLOGICAL INFORMATION 15.

**REGULATORY INFORMATION 16. Other information** 

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

#### Prepared for:

FPPF Chemical Company, Inc. 117 West Tupper Street Buffalo, NY, USA 14201 Telephone: 1-800-735-3773

Please direct all enquiries to FPPF Chemical Company

#### Prepared by:

ICC The Compliance Center Inc.

Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)

http://www.thecompliancecenter.com



# **DISCLAIMER**

This Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from FPPF Chemical Company, Inc and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and FPPF Chemical Company, Inc.

#### END OF DOCUMENT