

# **Safety Data Sheet**

Copyright,2019,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 29-3593-0
 Version Number:
 5.00

 Issue Date:
 06/04/19
 Supercedes Date:
 01/30/19

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Rubbing Compound PN 05973, 05974, 05968, 3900, 39002, 39002S, 39005

#### **Product Identification Numbers**

LB-K100-0959-1, LB-K100-0959-2, LB-K100-0961-4, LB-K100-0960-9, LB-K100-0954-8, LB-K100-0933-1, LB-K100-0933-2, LB-K100-0961-0, LB-K100-0961-1, 60-4550-5785-5, 60-4550-5787-1, 60-4550-5806-9, 60-4550-6559-3, 60-4550-7122-9, 60-4551-0213-1, 60-4551-0214-9, 60-4551-0215-6, 60-4551-0216-4 7000120042, 7000021276, 7000120073, 7100159911, 7100168978, 7100169724, 7100177111

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Automotive, Rubbing Compound

1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Automotive Aftermarket

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

# 2.1. Hazard classification

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

#### Signal word

Danger

### **Symbols**

Exclamation mark | Health Hazard |







#### **Hazard Statements**

May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure: respiratory system

### **Precautionary Statements**

#### General:

Keep out of reach of children.

#### **Prevention:**

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

# **Response:**

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Get medical advice/attention if you feel unwell.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

1% of the mixture consists of ingredients of unknown acute oral toxicity.

2% of the mixture consists of ingredients of unknown acute inhalation toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	30 - 60 Trade Secret *
Silica	7631-86-9	15 - 40 Trade Secret *
HYDROTREATED LIGHT PETROLEUM	64742-47-8	10 - 30 Trade Secret *
DISTILLATES		
Kaolinite	1318-74-7	3 - 7 Trade Secret *
Oleic Acid	112-80-1	1 - 5 Trade Secret *
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	1 - 5 Trade Secret *
Glycerin	56-81-5	< 2 Trade Secret *
Illite	12173-60-3	0.5 - 1.5 Trade Secret *
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	< 1 Trade Secret *
Poly(Oxyethylene)Sorbitan Monostearate	9005-67-8	0.1 - 1 Trade Secret *

SOLVENT DEWAXED LIGHT PARAFFINIC	64742-56-9	< 1 Trade Secret *
DISTILLATES (PETROLEUM)		
Alkyloammonium Salt	Trade Secret*	< 0.2 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

Non-combustible. Use a fire fighting agent suitable for surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum, insoluble compounds	1318-74-7	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
			mg/m3	carcin
Glycerin	56-81-5	OSHA	TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	
Mineral oils (untreated and mildly	64742-55-8	ACGIH	Limit value not established:	A2: Suspected human
treated)				carcin., Cntrl all exposr-
				low as possib
Paraffin oil	64742-55-8	OSHA	TWA(as mist):5 mg/m3	
Mineral oils (untreated and mildly	64742-56-9	ACGIH	Limit value not established:	A2: Suspected human
treated)				carcin., Cntrl all exposr-
				low as possib
MINERAL OILS, HIGHLY-	64742-56-9	ACGIH	TWA(inhalable fraction):5	A4: Not class. as human
REFINED OILS			mg/m3	carcin
Paraffin oil	64742-56-9	OSHA	TWA(as mist):5 mg/m3	
Paraffin oil	64742-65-0	OSHA	TWA(as mist):5 mg/m3	
PETROLEUM DISTILLATES	64742-65-0	OSHA	TWA:2000 mg/m3(500 ppm)	
SILICA, AMORPHOUS	7631-86-9	OSHA	TWA concentration:0.8	
			mg/m3;TWA:20 millions of	
			particles/cu. ft.	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

# Eye/face protection

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - Neoprene

#### **Respiratory protection**

**Vapor Density** 

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Odor, Color, Grade: Tan liquid. Slight solvent odor.

**Odor threshold**No Data Available

Odor tireshold

pH 7.5 - 8.5
Melting point Not Applicable
Boiling Point 98.3 °C

Flash PointNo flash pointEvaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor PressureNo Data Available

**Density** 1.2 g/ml

Specific Gravity 1.2 [Ref Std:WATER=1]

Solubility in Water Negligible

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data Available

Viscosity 6,000 - 18,000 centipoise [Test Method:Brookfield] [Details:#6

No Data Available

3M™ Rubbing Compound PN 05973, 05974, 05968, 3900, 39002, 39002S, 39005

06/04/19

Spindle]

Hazardous Air Pollutants 0.00002 lb HAPS/lb solids [Test Method: Calculated]

Molecular weight No Data Available

**Volatile Organic Compounds**213 g/l [*Test Method*:calculated SCAQMD rule 443.1] **Volatile Organic Compounds**15.2 % weight [*Test Method*:calculated per CARB title 2]

Percent volatile 58.3 % weight

VOC Less H2O & Exempt Solvents 415 g/l [Test Method:calculated SCAQMD rule 443.1]

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

#### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

Sparks and/or flames

#### 10.5. Incompatible materials

None known.

# 10.6. Hazardous decomposition products Substance

SubstanceConditionCarbon monoxideAt Elevated TemperaturesCarbon dioxideAt Elevated Temperatures

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May cause additional health effects (see below).

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eve Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

# **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### **Additional Health Effects:**

# Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

# Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Generic: Mineral oils (untreated and mildly treated)	64742-55-8	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Generic: Mineral oils (untreated and mildly treated)	64742-55-8	Known human carcinogen	National Toxicology Program Carcinogens
Generic: Mineral oils (untreated and mildly treated)	64742-56-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Generic: Mineral oils (untreated and mildly treated)	64742-56-9	Known human carcinogen	National Toxicology Program Carcinogens

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

# **Acute Toxicity**

Name	Route	Species	Value
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Rabbit	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation- Vapor (4 hours)	Rat	LC50 > 12 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolinite	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolinite	Ingestion	Human	LD50 > 15,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 4 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Oleic Acid	Dermal	Guinea pig	LD50 > 3,000 mg/kg
Oleic Acid	Ingestion	Rat	LD50 57,000 mg/kg
Poly(Oxyethylene)Sorbitan Monostearate	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly(Oxyethylene)Sorbitan Monostearate	Ingestion	Rat	LD50 > 62,640 mg/kg
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Dermal	Rabbit	LD50 > 5,000 mg/kg
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Inhalation- Dust/Mist	Rat	LC50 > 4 mg/l

3M <sup>TM</sup> Rubbing Compound PN 05973, 05974, 05968, 3900, 39002, 39002S, 3900
---

06/04/19

	(4 hours)		
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
(PETROLEUM)	_		
Alkyloammonium Salt	Ingestion	Rat	LD50 > 5,385 mg/kg
Alkyloammonium Salt	Dermal	similar	LD50 estimated to be > 5,000 mg/kg
		health	
		hazards	

ATE = acute toxicity estimate

# **Skin Corrosion/Irritation**

Name	Species	Value
Silica	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Kaolinite	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Glycerin	Rabbit	No significant irritation
Oleic Acid	Rabbit	Minimal irritation
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Rabbit	Minimal irritation
Alkyloammonium Salt	Rabbit	No significant irritation

Serious Eve Damage/Irritation

Serious Eye Damage/Hittation		
Name	Species	Value
Silica	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Kaolinite	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Glycerin	Rabbit	No significant irritation
Oleic Acid	Rabbit	Mild irritant
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Rabbit	No significant irritation
Alkyloammonium Salt	Rabbit	No significant irritation

# **Skin Sensitization**

Name	Species	Value
Silica	Human	Not classified
	and	
	animal	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Guinea	Not classified
	pig	
Glycerin	Guinea	Not classified
	pig	
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Guinea	Not classified
	pig	
Alkyloammonium Salt	Mouse	Sensitizing

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Silica	In Vitro	Not mutagenic
Oleic Acid	In Vitro	Some positive data exist, but the data are not sufficient for classification
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	In vivo	Not mutagenic
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	In Vitro	Some positive data exist, but the data are not sufficient for classification

Alkyloammonium Salt In Vitro Not mutagenic
--

Carcinogenicity

Name	Route	Species	Value
Silica	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
Kaolinite	Inhalation	Multiple	Not carcinogenic
		animal	
		species	
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not
			sufficient for classification
Oleic Acid	Dermal	Mouse	Not carcinogenic
Oleic Acid	Ingestion	Rat	Not carcinogenic
Oleic Acid	Not	Multiple	Not carcinogenic
	Specified	animal	
		species	
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES	Dermal	Mouse	Some positive data exist, but the data are not
(PETROLEUM)			sufficient for classification

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Alkyloammonium Salt	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Alkyloammonium Salt	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Alkyloammonium Salt	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	gestation into lactation

# Target Organ(s)

# Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Kaolinite	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolinite	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Glycerin	Inhalation	respiratory system   heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system   hematopoietic system   liver	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years

		kidney and/or bladder				
Oleic Acid	Ingestion	liver   immune system	Not classified	Rat	NOAEL 2,250 mg/kg/day	108 weeks
Oleic Acid	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,550 mg/kg/day	108 weeks
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Dermal	hematopoietic system   liver   kidney and/or bladder	Not classified	Rabbit	NOAEL 5,000 mg/kg/day	3 weeks

**Aspiration Hazard** 

Name	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

#### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

#### 15.1. US Federal Regulations

Contact 3M for more information.

#### **EPCRA 311/312 Hazard Classifications:**

Physical Hazards

06/04/19

Not applicable

#### **Health Hazards**

Respiratory or Skin Sensitization

Specific target organ toxicity (single or repeated exposure)

# 15.2. State Regulations

Contact 3M for more information.

#### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

# 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

#### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 29-3593-0
 Version Number:
 5.00

 Issue Date:
 06/04/19
 Supercedes Date:
 01/30/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

#### 3M USA SDSs are available at www.3M.com